

2310120056

## KSML-92

Flush mount keyboard, IEC60945 compliant



- ✓ Certificate of Conformity fully compliant with IEC60945
- ✓ IP67 sealing keyboard
- ✓ Compact layout with integrated numpad
- ✓ High brightness LED's with fibre optics
- ✓ Two dedicated keys for up/down dimming
- ✓ Low power LED's warrant for a long life
- ✓ No external power supply needed for the backlight
- ✓ The illumination intensity is dimmable
- ✓ Intelligent intensity setting of "Numlock" and "Capslock" LEDs
- ✓ White backlighting as standard, other colours on request

## Description

This 92 key backlit keyboard is approved for use with with Solas Marine applications (f.i ECDIS) Illumination of the key legends, contour and trackball contour with long life, low power LED backlighting using fiber optics techniques. The keyboard features a compact full MF keyboard with integrated numpad and a large 50mm laser trackball with removable ball. Front panel mounting with holes (for countersunk M4 screws, not included) or enclosed version. The added silicon sponge seal assures the sealing into the user's cabinet. The rear side components are protected by a covering metal plate.

# Specifications

## GENERAL

Sealing	IP65 sealed
Keys	92 short travel switches, tactile feel switches with 0,3 mm travel and 2,55 N operating force
Pointing Device	50 mm laser trackball, epoxy resin ball
Output	USB output for keyboard and trackball. Via shielded cable of 1,6 meter.
Compass safe distance	0,5 m
Operating temp.	0°C to +60°C
Material	Aluminium carrier and silicone sponge panel sealing
Power requirements	Directly from USB port
Front layer	Black polyester front layer with embossed keys, scratch and chemical resistant
Dimensions, (WxHx D)	385x185x50mm
Weight	1,2 kg