

2320005016

FM to IP gateway 8x

FM to IP Gateway 8x



Description

The FM to IP Gateway 8x is a universal solution for receiving, decoding, and multicast or unicast streaming of FM radio channels. The key advantages of the FM to IP Gateway are its high density and compactness - the 1U rack-mount server can receive and decode 8 FM radio stations with 4 FM antenna inputs located at the rear panel of the appliance. It is used together with the IPTV Server 8000.

Specifications

INTERFACES

Input	4x FM antenna input for receiving 8x FM radio stations
	Input frequency range: 88-108 MHz
Output	1x Gbit IP output, TS over UDP protocol, unicast and multicast

PHYSICAL & POWER

Mounting	Rack Mountable, 1HU
Weight	4 Kg
Dimension (W x H x D)	482mm x 44mm x 455mm
Power supply	100 - 220 VAC, 50-60Hz
Max. Power consumption	25W

ENVIRONMENTAL DATA

Operating Temperature	0~45°C
Storage Temperature	-20~80°C
Humidity	10 ~ 90% noncondensing

Used With



IPTV Server 8000 v2

IPTV Server 8000 v2 with configuration, 8x DVB-S/S2/T/T2/C+8x CI slots, v2



IPTV Server 8000 v2 w/ 8TB

IPTV Server 8000 with configuration, 8TB, 8x DVB-S/S2/T/T2/C+8x CI slots, V2