

CE NVR 128 16 Image

2310120203

CE-NVR-128/16

Network video recorder, 128 ch. 16HDD slots

Description

- ✓ Pluggable HDD design provides a convenient HDD installation and maintenance way; Unique chassis based on patented design ensures environmental friendly and low-noise running.
 - ✓ Adopt professional embedded hardware and software, and pioneering dual-OS design to ensure the reliability of system running.
 - ✓ Support redundant power supply to improve the system stability.
 - ✓ Adopts ANR technology to enhance the storage reliability when the network disconnected.
 - ✓ Supports HDD hot swap with RAID0, RAID1, RAID5, RAID 6, and RAID10 storage scheme configurable.
 - ✓ Either normal or hot spare working mode is configurable to constitute an N+1 hot spare system
- HD Input
- ✓ Connectable to the third-party network cameras like ACTI, Arecont, AXIS, Bosch, Brickcom, Canon, ONVIF, PANASONIC, Pelco, PSIA, SAMSUNG, SANYO, SONY, Vivotek and ZAVIO.
 - ✓ Up to 128 IP cameras can be connected.
 - ✓ Support live view, storage, and playback of the connected camera at up to 12 megapixels resolution
- HD Output
- ✓ Simultaneous HDMI 1/VGA output as the main output and the HDMI 2 works as the auxiliary output.
 - ✓ Video outputs at up to 4K (4096×2160) resolution
 - ✓ Supports decoding up to 20 channels at 1080p resolution.

HD Storage

- ✓ Up to 16 SATA interfaces and 1 eSATA interface connectable for recording and backup

HD Transmission

- ✓ 4 self-adaptive 10M/100M/1000M network interfaces

Various Applications

- ✓ Centralized management of IP cameras, including configuration, information import/export, real-time information display, two-way audio, upgrade, etc.

- ✓ Connectable to smart IP cameras from VINGTOR-STENTOFON and the recording, playing back, and backing up of VCA alarms can be realized
- ✓ VCA detection alarm is supported
- ✓ VCA search for face detection, behavior analysis, people counting and heat map
- ✓ Supports starting record with one key.
- ✓ Realize instant playback for assigned channel during multi-channel display mode
- ✓ Smart search for the selected area in the video; and smart playback to improve the playback efficiency
- ✓ Supports HDD quota and group modes; different capacity can be assigned to different channels

Specifications

VIDEO / AUDIO INPUT

| | |
|---|--|
| IP video input: | 128-ch |
| Incoming/outgoing bandwidth | 512Mbps/512Mbps |
| Incoming/outgoing bandwidth (RAID mode) | 400Mbps/400Mbps |
| Protocol | VINGTOR- STENTOFON, ACTi, ARECONT, AXIS, BOSCH, BRICKCOM, CANON, HUNT, ONVIF (Version 2.5), PANASONIC, PELCO, PSIA, RTSP, SAMSUNG, SONY, VIVOTEK, ZAVIO |

VIDEO / AUDIO OUTPUT

| | |
|-----------------------|--|
| HDMI output | Two independent HDMI outputs of 4K resolution. Resolution: 4K (4096 × 2160), 4K (3840 × 2160) /30Hz, 2K (2560 × 1440) /60Hz, 1080p (1920 × 1080) /60Hz, UXGA (1600 × 1200) /60Hz, SXGA (1280 × 1024) /60Hz, 720p (1280 × 720) /60Hz, XGA (1024 × 768) /60Hz |
| VGA output | 1-ch. Resolution: 1080p (1920 × 1080) /60Hz, UXGA (1600 × 1200) /60Hz, SXGA (1280 × 1024) /60Hz, 720p (1280 × 720) /60Hz, XGA (1024 × 768) /60Hz |
| LCD output (optional) | One 7 inch LCD |
| Audio output | 1-ch. RCA (2.0 Vp-p, 1 KΩ) |

VIDEO & AUDIO DECODING

| | |
|----------------------|---|
| Video resolution | 12 MP/8 MP/7 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF |
| Synchronous playback | Up to 16 channels |
| Capability | 20-ch @ 1080p |

HARD DISK

| | |
|-----------|---|
| Interface | 16 SATA interfaces supporting hot-plug |
| Capacity | 1TB/2TB/3TB/4TB/5TB/ 6TB/8TB |

RAID

| | |
|-----------|--|
| Raid type | RAID 0, RAID 1, RAID 5, RAID 6, RAID 10 |
|-----------|--|

NETWORK MANAGEMENT

| | |
|-------------------|--|
| Protocol | IPv6, HTTPS, UPnP, SNMP, NTP, SADP, SMTP, NFS, iSCSI, PPPoE, DDNS |
| Network interface | 4, RJ45 10M/100M/1000M self- adaptive Ethernet interface |

EXTERNAL INTERFACE

| | |
|---------------------|---|
| Two-way audio input | 1-ch, RCA (2.0 Vp-p, 1 KΩ) |
| Serial port | 1 RS-232, 1 RS-485, Keyboard |
| Serial interface | RS-232; RS-485; Keyboard |
| USB interface | Front panel: 2 × USB 2.0; Rear panel: 1 × USB 3.0 |
| Alarm input/output | 16/8 |

GENERAL

| | |
|---------------------------------|---|
| Power supply | 100 to 240 VAC, 550W |
| Fan | Redundant dull ball bearing fan; Speed adjustable; Hot-plug |
| Consumption (without hard disk) | ≤ 140W |
| Working temperature | 0 °C to 50 °C (32 °F to 122 °F) |
| Working humidity | 10 to 90 % |
| Chassis | 19-inch rack-mounted 3U chassis |
| Dimensions (W × D × H) | 442 × 494 × 146 mm (17.4 × 19.4 × 5.7 inch) |
| Weight (without hard disk) | ≤16 kg (35.3 lb) |

HARDDISK

| | |
|------------|---|
| 2310120062 | CE-NVR-WD20PURZ HDD 2TB, 3,5" SATA 24/7 |
| 2310120063 | CE-NVR-WD40PURZ HDD 4TB, 3,5" SATA 24/7 |
| 2310120064 | CE-NVR-WD60PURZ HDD 6TB, 3,5" SATA 24/7 |
| 2310120065 | CE-NVR-WD80PURZ HDD 8TB, 3,5" SATA 24/7 |

Accessories



DS-1005KI

USB joystick and keyboard



CE-NVR-WD20PURZ
HDD 2TB

2TB, 3,5" SATA 24/7 HDD
Drive



CE-NVR-WD40PURZ
HDD 4TB

4TB, 3,5" SATA 24/7 HDD
Drive



CE-NVR-WD80PURZ
HDD 8TB

8TB, 3,5" SATA 24/7 HDD
Drive