



2200001142

FXS-8104

A powerful analog telephone adapter

- Supports 2 SIP profiles and 4 FXS ports
- TLS and SRTP
- Automated & secure provisioning
- 3-way voice conferencing per port
- ✓ Supports T.38 Fax
- Failover SIP server
- Supports dual Gigabit network ports
- Includes a built-in NAT router

Description

The Vingtor-Stentofon FXS-8104 is an advanced 4-port VoIP gateway with 4 FXS ports and an integrated Gigabit NAT router. This powerful gateway features exceptional voice quality in various application environments, strong encryption with unique security certificate per unit, automated provisioning for volume deployment and device management, and outstanding network performance for home and office use.

Specifications

GENERAL

Dimension	28.5mm(H) x 130mm(W) x 90mm(D)	
Weight	0.29 Kg	
Environmental	Operational: 32° – 104°F or 0° – 40°C; Storage: 14° – 140°F or -10° – 60°C; Humidity: 10 – 90% Non- condensing	
Power Supply	Input: 100-240VAC, 50- 60Hz; Output: 12V/1.0A	
Telephone Interfaces	Four(4) RJ11 FXS ports	
Network Interfaces	2 x 10/100/1000Mbps RJ45 ports	
LED Indicators	POWER, LAN, WAN, PHONE1, PHONE2, PHONE3, PHONE4	
Telephony Features	Caller ID display or block, call waiting, flash, blind or attended transfer, forward, hold, do not disturb, 3-way conference	
Voice Codecs	G.711 with Annex I (PLC) and Annex II (VAD/CNG), G.723.1, G.729A/B, G.726, iLBC, OPUS, dynamic jitter buffer, advanced line echo cancellation	
Fax Over IP	T.38 compliant Group 3 Fax Relay up to 14.4kpbs and auto- switch to G.711 for Fax Pass-through	
Short/Long Haul Ring Load	2 REN, up to 1km on 24AWG line	

page 2/3

DTMF-based CID	
Busy Tone, Polarity Disconnect Methods Reversal/Wink, Loop Current	
TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP/RARP, ICMP, DNS, DHCP, NTP, TFTP, SSH, STUN, SIP (RFC3261), SIP over TCP/TLS, SRTP, TR- 069	
QoS Layer 2 (802.1Q VLAN, SIP/RTP 802.1p) and Layer 3 (ToS, Diffserv, MPLS)	
DTMF Method In-audio, RFC2833 and/or SIP INFO	
Provisioning and Control HTTP, HTTPS, SSH, TFTP, TR-069, secure and automated provisioning using AES encryption, syslog	
Media SRTP	
Control TLS/SIPS/HTTPS	
Syslog support, SSH, Management remote management using web browser	
Compliance FCC/CE/RCM, K.21	