

3006204094

MP-114

SIP gateway 4 port FXO

This product has been replaced by MP-114-V2



Description

- ✓ Connects Vingtor-Stentofon AlphaCom XE system to external telephone systems such as PABXs and the public telephone network
- ✓ Possible to share a gateway between multiple AlphaCom XE nodes (require VoIP AlphaNet license)
- ✓ High audio quality supporting echo cancelling and default simplex switching
- ✓ Web management for easy configuration and installation
- ✓ Cost effective trunking
- ✓ 4 port FXO

Specifications

GENERAL

Usage	Analogue telephone gateway
Telephone interface	FXO Loop-start
Temperature range	Storage: -25° to 85°C / Operational: 5° to 40°C
Humidity range	10% to 90% non-condensing
Dimensions (WxHxD)	220 x 42 x 172mm / 8.67 x 1.66 x 6.78 inches
Power	100 – 240 VAC / 50-60 Hz
Mounting	Rack mount with optional rack-mount kit Table top Wall mount
Ethernet Interface	10/100 Mbps, Base-Tx, RJ45
Network QoS	DiffServ, TOS
IP transport	RFP / RTCP per IETF RFC 3550 and 3551
Calling Line Identity	Bellcore Type 1 & 2, ETSI, BT, NTT and DTMF-based CID (Brazil, Denmark, India, Netherlands, Sweden)
In-band signalling	DTMF (TIA 464B) User defined and call progress tones
EMC compliance	EN55022 Class B, CFR Part 15 Class B, EN55024, EN61000-3-3, EN61000-3-2, VCCI Class X1 (equal to class B)
	EN60950-1 Safety of IT equipment, UL60950-1

Safety compliance	Including compliance to section 6 (over-voltage protection)
Telecom compliance	TRR-21, TIA-968
Call routing	Two stage dialing, Line hunting, Prefix line selection