



Compact ICS

Integrated Communication System

- $\begin{tabular}{ll} \hline \end{tabular} \begin{tabular}{ll} \hline \end{$
- ✓ IP-22 Rating
- Capacity: Up to 72 lines
- Oual power supply: AC/DC or AC/AC



SIP



Onboard communication

Description

The flexible configuration of the Compact ICS provides a cost effective solution for intercom, telephone, Public Address and loudhailing. The modern architecture offers network connection including cascading, remote service and interface to/from other IP based systems and components. The Compact ICS system is compatible with all existing intercom stations and offers a unique combination of analog, digital and IP based communication terminals. By adding the ICS P-6202 Billing Unit, logging and billing of calls are trackable using PIN and extension registration.

page 1/2

certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

Specifications

MECHANICAL

Dimensions (WxHxD)	618x585x470 mm	
Weight	30 kg	
PRODUCT VARIANTS		
PRODUCT VARIANTS		
4000019779	Compact ICS 24 lines, AC/DC	
4000019780	Compact ICS 24 lines, AC/AC	
4000019781	Compact ICS 48 lines, AC/DC	
4000019782	Compact ICS 48 lines, AC/AC	
4000019823	Compact ICS 72 lines, AC/DC	
4000019824	Compact ICS 72 lines, AC/AC	

page 2/2