

4000018361 / 4000100030

ICS 6200

Central Unit



- Up to 24 analog or digital lines per unit
- 48 VoIP registrations per unit
- 2 x 100 Mbit Ethernet ports
- Modular terminal interface design
- PBX features such as group calls, paging groups, alert groups, conferences, switchboard, direct inward dialling
- ✓ VoIP or FXO trunk lines
- SIP/RTP protocol support
- Dual redundant power supply
- Omplies with IEC 60945 Standard for Marine Equipment
- ONV-GL, ABS, RMRS type approval and compatible with NORSOK

Description

The Phontech P-6200 Central Unit is a digital communication system meeting all aspects of internal and external communication, and information exchange on-board vessels, offshore installations and to/from onshore operation centers.

Up to six line boards can be added with the following interface formats:


- 4000017689 6200 FXS line board, 4 analogue lines
- 4000017839 6200 UpN line board, 4 digital lines
- 4000017836 6200 FXO line board, 4 analogue trunk lines
- 4000017838 6200 E&&M line board 2 lines (4wire)

For systems that are not using purely IP extensions we recommend to also use the ICS 6205 RJ45 to D-sub patch panel (item no. 4000018364), cable organizer (item no. 4000018586) as well as our eight-line termination module kit (item no. 4000018526).

Technical Dimensions

certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is



page 2/3

Specifications

MECHANICAL

Dimensions	19" 1U rack mounted, D=246 mm
Weight	3.5 kg
Color	RAL 9005
Material	Steel / Plastic
Mounting	Rack/ Console
Fixing	2 x M5 bolts
Access	Front
Cable Entry	Rear and Front
Connector Type	RJ45

ELECTRICAL

Power Supply	220/110 VAC, 48/24 VDC (dual redundant)
Power Consumption	12 W (idle), 65 W (max)
Heat Dissipation	35 W (max)
Compass Safe Distance	0.2 m

ENVIRONMENTAL

Temperature	0°C to +55°C
Humidity	+93% (at +40°C)
Ingress Protection Rating	IP-20

PRODUCT VARIANTS

4000018361	ICS 6200 Basic Unit AC/DC Power
4000100030	ICS 6200 Basic Unit AC/AC Power
1150103009	ICS 6200 Basic Unit AC/DC Power w/installation, incl. patch panel, cable organizer and patch cable
1150103010	ICS 6200 Basic Unit AC/AC Power w/installation, incl. patch panel, cable organizer and patch cable

page 3/3