

4000200500

P-6212

Industrial Telephone





Description

- ✓ Integrated loudspeaker/microphone
- ✓ Hands-free, duplex communication
- ✓ 2" Graphic backlit display:
 - ✓ Menus and navigation wheel/key
 - ✓ Contact list
 - ✓ Caller ID
- ✓ Dimmable backlight (keypad)
- ✓ Privacy switch (Do not disturb) with priority override
- ✓ Manual PTT (push-to-talk) key
- ✓ 3 pcs programmable direct access keys (A-B-C)

- ✓ Volume adjustment with override
- ✓ Speakerphone SPL level >85dB(A) (integrated loudspeaker)
- ✓ Bulkhead mounted
- ✓ MMI according to IEC 62288 Ed 2.0
- ✓ Status/health indicator
- ✓ Multiple ring melodies
- ✓ Integrated call relay for external signal device
- ✓ Output to external loudspeaker, 8 W, SPL level > 110dB (loudspeaker dependent)
- ✓ Headset connection
- ✓ Complies with IEC 60945 Standard for Marine Equipment
- ✓ DNV/ABS/RMRS/CCS type approval and compatible with NORSOK

The P-6212 is intended for installation outdoors or in harsh environments inside. This is a UpN digital station with loudspeaker, internal microphone, memory functions, etc. It is equipped with an amplifier for an additional external loudspeaker and a relay for external call signal devices (beacons, sirens, etc.).

Technical Dimensions



UpN connections

Specifications

MECHANICAL

Dimensions (WxHxD)	144 x 216 x 91.3 mm
Weight	1 kg
Material	Plastic (PC/ASA)
Color	Grey – RAL 7021/7043
Mounting	Bulkhead / Direct or Bracket
Fixing	4 x M4 bolts
Access	Front
Cable Entry	Side / Bottom – through Glands (optional)
Connector Type	Terminals (P2.8/P2.9, screen P2.10)

ELECTRICAL

Power Supply	System / Line feed (Basic telephone operation). Additional 24V/1.5A input for call relay and amplifier for external loudspeaker.
Line Format	UpN (Digital 2Wire – 2B+D)
Power Consumption	10W (max – external loudspeaker)
Termination	Line: RJ45, two center cores. External loudspeaker/external signal device, etc: clamp terminals.
Compass Safe Distance	>5 m
External loudspeaker	8W / 20Ω
External signal device, Call relay	6.3 A (max)

ENVIRONMENTAL

Temperature	-25°C to +55°C
Humidity	+93% (at +40°C)
Ingress Protection Rating	IP-56 (exposed)
UL94	V0

Accessories



P-6035/10

Headset with 10-meter
Cable