



2211100117

## 7622 DECT Handset

DECT Handset, IP64

---

### Description

The 7622 handset is highly durable, designed specifically for manufacturing environments, and comes with a range of features such as an alarm button, color display, and manufacturing-specific alarm icons.

- ✓ Robust operation and handling, IP64
- ✓ Exceptional voice quality without any background noise, echo, delay, or interruptions
- ✓ Color Display
- ✓ 12 different ringtones and vibration alert
- ✓ Advanced messaging
- ✓ Alarm Key
- ✓ Headset jack with amplifier for industrial headsets
- ✓ Handsfree
- ✓ Instant notifications make users aware of potentially hazardous situations
- ✓ Lone workers can send alarms in case of emergency

# Specifications

## GENERAL

|                       |   |
|-----------------------|---|
| Size                  | 148 x 50.4 x 21.6 mm  |
| Weight                | 115 g incl. battery   |
| Operating temperature | -10 - 55° C   |
| Charging temperature  | 0° - 40° C  |
| Speech time           | up to 23 (27 hours in economy mode)   |
| Standby time          | up to 118 hours   |
| Approvals             | EMC: EN 301 489-1, EN 301 489-6, Radio: EN 301 406; Safety: EN 60950-1; Drop test: IEC 60068-2-32; According to EN60529: IP 64 classified |
| Frequency Range       | EMEA 1880-1900 MHz  |

## ACCESSORIES

|            |   |
|------------|---|
| 2211100125 | Belt clip for 72 series and 76 series                     |
| 2211100556 | Charger kit for 7212, 7622 & 7642                         |
| 2211100601 | Spare Battery rechargeable for 72, 76-series DECT handset |

## Accessories



## DECT Headset Image

### Headset for DECT handset V2

Headset

## DECT Charger

Charger kit for 72-series,  
76-series DECT Handsets.  
Includes Power Supply  
100-240V

## Used With



### KWS6500

IP DECT Server for 30  
users, including software  
licence



### IP DECT Base Station

IP Base Station for  
KWS6500



### IP DECT Server 400 1G8 Version

Server Base Station