

2220010055

BC00224FE

12 port SC patchpanel Singlemode complete with plugs



Description

This is innovative, robust 1U sliding patch panel. These panel include an internal mounting plate to install the Adaptors giving a reduction in the bend radius of the exiting patch cords also giving more astatically pleasing installation. With the ability to use a full array of adaptor types offering a flexible solution to the end user, enabling them to incorporate a multi functional panel which allow easy access during installation or re-work with no disturbance of the existing cable or fibres.

In the addition to the array of adaptors the panel also offers multiple cable entry solutions, up to 4 standard cable entry points for loose tube, tight buffer, pre terminated and steel tape armoured cable. Each panels has integrated strength member tie positions also with the additional removable plate at the rear of the panel allows the installation of steel tape armoured cable.

Specifications

FEATURES

Up to 48 fibres in 1U

Multiple Adaptor options
available

24 Adaptor positions - 12
Used

Recessed Adaptor
positioning

Individually labelled ports

45° open working angle

Accepts loose tube,
distribution and pre
terminated cables

RoHS, REACH SvHC and
UL rated

Fits standard 19"

SPECIFICATION

Size	1U (44.4mm)
Net weight	2.5 KG
IP rating	IP20
Suitable for Adaptor type	SC
Number of ports	12
Cable Entry 20mm	2
Cable Entry 25mm	2
Mounting Adjustment rang	50mm
Material	Cold- rolled steel
Material thickness	1.2 mm
Material coating	Powder coating
Colour	RAL 9004
Operating temperature	-40°C to +50°C
Designed in accordance with	TIA/EIA 568.C, ISO/IEC 11801, EN50173, IEC60304, IEC61754,EN297-1
Compliant to	RoHS, Reach/SVHC

DIMENSIONS

Height	55 mm
Width	450 mm
Depth	260 mm