

SPA-W1AR-V2 Front

3005010196

SPA-W1AR-V2

Weatherproof PA and Alarm Panel



IP66

Description


- Weatherproof PA and Alarm Panel
- Panel for single system
- General alarm
- Built-in pre-amplifier with preset signal level and tone controls.
- Buttons with hinged transparent protecting cover
- Requires microphone with push to talk (PTT)
- Replaceable text label to each button
- ✓ Plug for WP handheld microphone P-66 or P-66/10
- Wall mounting outdoor / Indoor
- Local mute contact for external loudspeaker (from hardware version 4.0)

This weatherproof panel is a combined panel for General Alarm and All Call Message. For use in SPA-V2 Public Address and General Alarm Dual System.

Local mute function is used to break audio to loudspeakers where proximity to pa panel cause feedback. Available from hardware version 4.0 This function must be in combination with relay box.

Technical Dimensions

page 1/3



page 2/3

Specifications

GENERAL

Size (WxHxD)	140 x 230 x 125
Weight	0. 5 kg
Material	ABS plastic
Mounting	Wall
Output signal	0.775Vrms / 0dB
Sensivity microphone	200 ohm / 0,5mV
Connections	Plugable screw terminals for 2.5 mm 2 cable
Cable glands	2 x PG-16
Cable size	6 x 2 x 0.75mm2
Protection	IP-66
Operating temperature	-25°C TO +55°C
Environmental Condition	Exposed

Accessories





P-66

Handheld Microphone Waterproof

P-66/10

Handheld Microphone with 10-Meter Cable Waterproof