


2220012103

C9200L-48T-4X-E

Cisco C9200L 48port GE switch with 4x10G SFP+, 3yDNA, NE



CISCO Certified

Description

Cisco Catalyst 9200 Series switches extend the power of intent-based networking and Catalyst 9000 hardware and software innovation to a broader set of deployments. With its family pedigree, Catalyst 9200 Series switches offer simplicity without compromise – it is secure, always on, and IT simplified.

As foundational building blocks for the Cisco Digital Network Architecture, Catalyst 9200 Series switches help customers simplify complexity, optimize IT, and reduce operational costs by leveraging intelligence, automation and human expertise that no other vendor can deliver regardless of where you are in the intent-based networking journey.

Catalyst 9200 Series switches provide security features that protect the integrity of the hardware as well as the software and all data that flows through the switch. It provides resiliency that keeps your business up and running seamlessly. Combine that with open APIs of Cisco IOS XE and programmability of the UADP ASIC technology, Catalyst 9200 Series switches give you what you need now with investment protection on future innovations.

With full PoE+ capability, power and fan redundancy, stacking bandwidth up to 160 Gbps, modular uplinks, Layer 3 feature support, and cold patching, Catalyst 9200 Series switches are the industry's unparalleled solution with differentiated resiliency and progressive architecture for cost-effective branch-office access.

Specifications

Cisco Catalyst C9200L-48T-4G-E is managed 48-port switch with 48 auto-sensing 10/100/1000 ports and 4x 10 Gigabit Ethernet SFP+ ports .

PORTS

10/100/1000 RJ45	48
10G SFP+	4
Console ports	RJ-45-to-DB9 cable for PC connections, USB-C adaptor, USB adaptor

ENVIRONMENT

Operating temperature	-5°to +45°C
Operating relative humidity	5% to 90% (non-condensing)

ELECTRICAL CHARACTERISTICS

Frequency	50 to 60 Hz
AC voltage	100 to 240 VAC
Power supply rated maximum	125W
Total output BTU (note:1000 BTU/hr = 293W)	426.5 BTU/hr
Maximum power Consumption	47.33W
Input current	1.6-0.7A

DIMENSIONS & WEIGHT

Dimensions (W x D x H)	445 x 288 x 44 mm
Weight	4.53 kg
Mounting	Rack Mountable, 1HU