

3005020010

CU-20

Central Unit for CTB-20 This product has been replaced by Phontech CIS Talk-Back System

This product will be replaced by the equivalent Phontech solution, but Zenitel will honor prior commitments given to the market. Therefore, we will continue to provide expansion and spare-part service for this product.



Description

- ✓ Central unit 20 lines for the CTB system
- ✓ Operates with CTB-20 and CTB-20 W/V01 panel units
- ✓ AUX / Alarm input
- ✓ Output to Public Address system
- ✓ 24 VDC power supply

Specifications

SPECIFICATIONS

| | |
|-----------------------------|---|
| Material / finish: | Aluminium / black |
| Mounting | Bulkhead with 4 x 4 mm screws |
| Terminals | Plugable screw terminals for cable max. 2.5 mm² |
| Fuses | F1, F2, F3, F4, 1 A 5 x 20 |
| DIP-switches | For PA-zones, set priority, set receive call |
| Pot.meter | For volume setting line 1-5, 6-10 |
| Dimension (mm) | 400W x 400H x120D |
| Weight | Approx. 2.6 kg |
| External connections | 4x Operation panels, up to 10 substations, AUX, PA |
| AUX input | 0 dB 0,775 V/600 ohm |
| Alarm contact | Potential free N/O |
| Frequency range | 200 Hz - 8 KHz (-3 dB) |
| Temperature operating | -15 to +55 °C |
| Power supply | 20 - 32 VDC |
| Power consumption at 24 VDC | 2.5 A |
| Output power | 30 W per 10 lines |
| Output impedance | 20 ohm per line |
| IP-rating | IP-20 |