

CAB-AVIP55-115/230

2810011068

CAB-AVIP55-115

Active IP55 ventilation for CABxx, 133mm heigh, 115VAC

- ✓ Roof-mounted fan 115V, 133 mm height
- ✓ Enclosure internal thermostat
- ✓ Thermostat Mounting plate
- ✓ Outlet filter Standard (255x255mm)

Description

CAB-AVIP55-115 is an active IP55 ventilation unit that is intended to be used with the CABxx cabinet range. With its IP55 protection, it is intended to be used in environmentally demanding areas. It can also be used on glazed door cabinets where an air inlet can be mounted on the side or on the back of the cabinet.

*Include filter mat for IP55 protection and internal thermostat with mounting plate, 417 m³/h

Specifications

ELECTRICAL DATA

Rated operating voltage	115 V, 1~, 60 Hz
Power consumption	At 60 Hz: 65 W
Air throughput, unimpeded air flow	At 60 Hz: 446 m³/h
IP protection	IP 55 including filter mat

DIMENSIONS & WEIGHT

Roof mounted fan dimensions (W x H x D)	400x133x400mm
Roof mounted fan mounting cut-out	258x258mm
Roof mounted fan installation depth	34.6 mm
Inlet filter dimensions (W x H x D)	255x255x25mm
Inlet filter mounting cut-out	224x224mm
Weight	5.76kg

Used With



CAB15F-V2

Floor cabinet 19" 15HU
600x600x800mm fixed frame



CAB24FW-V2

Floor cabinet 19" 24HU
800x600x1200mm fixed frame



CAB24FWD-V2

Floor cabinet 19" 24HU
800x800x1200mm fixed frame



CAB42F-V2

Floor cabinet 19" 42HU
600x600x2000mm fixed frame



CAB42FW-V2

Floor cabinet 19" 42HU
800x600x2000mm fixed frame



CAB42FWD-V2

Floor cabinet 19" 42HU
800x800x2000mm fixed frame



CAB24F-V2

Floor cabinet 19" 24HU
600x600x1200mm fixed frame



CAB24SW-V2

Floor-mounted 24HU cabinet -
800x1200x600mm (WxHxD)
swing frame



CAB42SWD-V2

Floor cabinet 19" 42HU
800x800x2000mm swing frame



CAB42FD-V2

Floor cabinet 19" 42HU
600x800x2000mm fixed frame



CAB42FWDD

Floor cabinet 19" 42HU
800x1000x2000mm fixed frame