

2810010114-CAB42FW-V2-Image

2810010114

CAB42FW-V2

Floor cabinet 19" 42HU 800x600x2000mm fixed frame

- Front metal door
- Front door handle: Double-bit lock
- Without rear door (available at request)
- Includes 2x side steel sheet panles
- Including 4x eyebolts for crane transportation
- The door hinged on the right, may be swapped to the left
- Base/plinth not included, can be ordered separately

Description

Our all-new series of multi-use cabinets are designed to be used in a marine environment. This floor-mounted 42HU cabinet is perfect for installing our 19" system components to create a complete system for your installation.

The cabinet comes with a front metal door that is hinged on the right, and it can be swapped to the left if needed. The rear side of the cabinet is covered with a fixed metal plate and can be replaced with rear doors if needed. Cabinet variant 42 HU, 800 wide and 600 deep. Internal 19-inch fixed frame for up to 42 HU. Includes the choice of DIN rail mounting in the bottom, prepared for optional power switch-over modules and terminals. Comes with 3 fixed door plates, front doors, and chassis ground.


By default, the cabinet is IP55 but the final IP rating will depend on the chosen ventilation options.

This cabinet is suitable for:

- ACM Advanced modules
- SPA-V2 Public address
- Radio
- ✓ LAN
- CCTV
- ✓ IPTV
- DECT
- Paging
- Masterclock

page 1/4

certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.



page 2/4

Specifications

GENERAL

Dimensions (WxDxH)	807x608x2164mm
Color	RAL 7035
Material	Steel
Ingress grade	IP-55 (or less, based on selected ventilation)
Mounting	Floor mounted
Cable inlet	Bottom (top available on request)
Environmental Condition	Protected

Accessories

CAB-DH-K

Door handle with key-lock for CABxx

CAB-DH-P

Door handle with push-button for CABxx

CAB-DH-PP

Door handle with push-button & pad-lock for CABxx

CAB-LED

CABxx LED System light w/sensor 100-240VAC, w/connection cable

CAB-CE-M


Cable entry gland 14xM25/32

CAB-CE-L

Cable entry gland 2xM25/32/40, 1xM32/40/50, 2xM40/50/160


CAB-CE-S

Cable entry gland w/sealing membranes Ø7 to 26mm



CAB-AVF-L-230

Active ventilation for CABxx with a steel door, 230VAC



CAB-AVF-L-115

Active ventilation for CABxx with a steel door, 115VAC

CAB-AVIP55-115/230

CAB-AVIP55-230

Active ventilation unit IP55 for CABxx, 133mm heigh, 230VAC

CAB-AVIP55-115/230

CAB-AVIP55-115

Active IP55 ventilation for CABxx, 133mm heigh, 115VAC

CAB-AVT-115-230

Active ventilation for CABxx with glass door, 115-230VAC

CAB-1GD-42

Cabinet glazed door 600x2000mm

CAB-1SD-42

Cabinet steel door 600x2000mm

Rittal Base-Plinth

CAB-BASE-86

Base / plinth for 800x600mm cabinets

page 4/4