

NGFW1010

2220012662

FPR1010-NGFW-K9/IEC60945

Cisco Firepower 1010 NGFW Appliance / IEC60945



CISCO Certified

Description

The Cisco Firepower® 1000 Series deliver business resiliency, management ease-of-use, and threat defense. They offer exceptional sustained performance when advanced threat functions are enabled. 1000 Series addresses use cases from small offices to remote branches. 1000 Series platforms run Cisco Threat Defense (FTD) and Cisco ASA software.

Specifications

INTERFACES

Integrated I/O	8 x RJ-45 (Includes 2 POE+ capable ports)
Integrated network management port	1 x 10M/100M/1GBASE-T Ethernet port (RJ-45)
Serial port	1 x RJ-45 console
USB	1 x USB 3.0 Type-A (500mA)

OPERATING PARAMETERS

Temperature	0 to 40 °C
Relative humidity	90 percent noncondensing

POWER INPUT (PER POWER SUPPLY)

AC range line voltage	External, 100 to 240 volts alternating current (VAC)
AC maximum input current	< 2A at 100V, < 1A at 240V
AC frequency	50/60 Hz

DESCRIPTION

Form factor	Desktop, shelf mountable
Dimensions (H x W x D)	46.22 x 199.39 x 204.98 mm
Weight (with AC power supply)	1,36 kg