

AK5850 Headset

AK5850BHS

AK5850BHS Ex TwinCom Headband Headset w/ear plug connector

Ex-approved Headset with headband

- Rugged headset for Ex and Industrial environments
- Noise-cancelling microphone
- High quality digital background noise reduction
- HD-voice compatible
- High quality audio
- Optional in-ear monitors may be connected for added damping in extreme environments
- Standard 4-pole Nexus connector for easy connection/replacement
- For use with Ex-approved and industrial plugboxwith PTT
- Low smoke and halogen free cable
- O Designed for Turbine Ex explosion-proof and industrial intercoms





ICX-AlphaCom (1)) Exigo



Description


The AK5850BHS is a high quality industrial Ex-approved headset for use in rugged conditions. It offers an adjustable boom microphone and a short curly cable for flexible connectivity through a 4-pole Nexus plug. This headset is designed for use with the Vingtor Stentofon Turbine Ex and Industrial Intercoms and are HD Voice compatible when used with these stations.

Used with the TAX-2B/TA-22B Cable and Plugbox with PTT, it offers an exceptional range of over 10 meters. The pluggable nature of the headset allows for easy maintenance/replacement as well as allowing operators to use their personal headset as a hearing protection aid, and disconnecting once the conversation is over.

Technical Dimensions

page 1/5

Last revision date: 2025-01-15 13:11



page 2/5

Specifications

MECHANICAL

Weight	400 g
ENVIRONMENTAL	
Operational Temperature	-40°C to +60°C
Ingress Protection (IP)	IP-54
ELECTRICAL	
Impedance	230 ohm
Sensitivity (mic)	4 mV / 220 ohm
ACOUSTICAL	
Frequency Response	90-7000 Hz
Noise Reduction	-12dB @ 1kHz

AK5850BHS Over-the-head headband TwinCom with custom molded earplug

SOUND ATTENUATION

Above 1kHz:	36 to 49 dB
500-1000 Hz	38.6 to 39.3 dB
125-500 Hz	30.0 to 38.6 dB
H84	34 dB
M84	34 dB
L84	29 dB
SNR84	36 dB

CERTIFICATIONS

CENELEC safety standards	EN 60079-0: 2018 & EN 60079-11: 2012
IEC safety standards	IEC 60079-0: 2018, IEC 60079-11: 2012
Marking	Ex ib IIC T4 Gb, Ta:-40°C to +60°C
ATEX certificate	Nemko 03ATEX1351 Issue 9
IECEx certificate	IECEx PRE 15.0063 Issue 2
PPE	(EU) 2016/425 (EN 352-1:2020, EN 352-2:2020, EN 352-2:2020 and EN 352-9:2020)

Accessories

page 3/5



TAX-2B

Ex-Approved Plugbox & Dry Cable for Headset with PTT



TA-22B

Industrial Plugbox & Cable for Headset with PTT



Spare Boom Microphone for Headset

Spare Boom Microphone for all A-Kabel type Headsets

Used With



EAPFX-6-V2

Exigo Industrial Ex Access Panel, 6 Buttons - V2

1008123030 TFIX-3-V2

TFIX-3-V2

Ex IP Intercom Station with 3 buttons



EAPFX-1-V2

Exigo Industrial Ex Access Panel - V2

IP and SIP Intercom

TFIE-1

IP and SIP Intercom

1008123010 TFIX-1-V2

TFIX-1-V2

Ex IP Intercom Station- full keypad

1008123010 TFIX-1-V2

TFIX-2-V2

Ex IP Intercom Station with 6 buttons

IP and SIP Intercom

TFIE-2

IP and SIP Intercom



EAPII-1

Exigo Industrial Access Panel, 1 Button

page 4/5



EAPII-6

Exigo Industrial Access Panel, 6 Buttons

IP and SIP Intercom

TFIE-6

IP and SIP Intercom

page 5/5