

tbd

SPCB-15W-50-EN54

2-WAY BASS REFLEX FLUSH MOUNT CEILING SPEAKER


- ✓ EN 54-24 CERTIFIED
- ✓ HIGH QUALITY AUDIO FOR VOICE AND BACKGROUND MUSIC
- ✓ 15W / 100V
- ✓ LOW IMPEDANCE OPTION
- ✓ 2-WAY BASS REFLEX CEILING SPEAKER WITH NEODYMIUM TWEETER
- ✓ IMPACT RESISTANT ABS HOUSING



Public Address



Voice Alarm

Commercial Audio

EN54

EN 54 Certified

Description

The SPCB-15W-50-EN54 is a 15W 100V 2-way bass reflex ceiling loudspeaker with neodymium tweeter. It has a 5" (130mm) loudspeaker chassis providing excellent sound quality for speech and background music. Certified to EN 54-24 the speaker is fitted with a 100V transformer with four power level adjustment tapings of 15W, 7.5W, 3.75W and 1.9W. Low impedance operation is also possible.

The impact-resistant ABS housing in RAL 9016 guarantees long-term stability. For additional reliability, a thermal fuse and a strain relief fitting are provided. The speaker is protected to class IP21C and the speaker chassis is treated against damp. Easy installation is made possible through a simple screw mounting system.

The loudspeaker is optionally available with a DC blocking capacitor fitted, in order to provide compatibility with DC loudspeaker line monitoring systems. The part number for this DC monitoring compatible version is SPCB-15W-50-EN54-DC.

Used With



V2000

PAVA 2000W Power Amplifier
Mainframe (0 amps Pre Installed)

from site

D150

PAVA 150W Power Amplifier
Module for the V2000 / INTEGRA

from site

D500

PAVA 500W Power Amplifier
Module for the V2000 / INTEGRA