

DS-6701HUHI One channel Video to IP encoder Image

2310111166

DS-6701HUHI One channel Video to IP encoder

Encoder

- ✓ Self-adaptive HDTVI/HDCVI/AHD/CVBS signal input
- ✓ Up to 5 MP HDTVI video input and live view
- ✓ Full channel recording at up to 5 MP resolution



H.264

Description

The DS-6701HUHI One channel Video to IP encoder features self-adaptive HDTVI/HDCVI/AHD/CVBS signal input with up to 5 MP HDTVI video input and live view and long distance transmission over UTP and coaxial cable.

The encoder features H.265+/H.265/H.264+/H.264 encoding for the main stream, and H.265/H.264/MJPEG for the sub-stream of analog cameras.

DS-6701HUHI One Channel Video to IP Encoder

It has a 1 micro SD card slot (8G up to 128 GB capacity) that allows for searching and playing back recorded files by camera number, recording type, start time, end time, etc. It supports smart functions including line crossing detection, intrusion detection, sudden scene change detection, and audio exception detection.

Technical Dimensions



Specifications

DESCRIPTION

| | |
|----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Video Compression | MJPEG (sub-stream)/H.265+/H.265/H.264+/H.264 |
| Video input | 1-ch, BNC (1.0 Vp-p, 75 Ω), supporting coaxitron connection |
| Audio compression | G.711u |
| Audio input | 1-ch, 3.5mm interface (2.0 Vp-p, 1 kΩ) (LINE IN) |
| Two-way audio | 1-ch, RCA (2.0 Vp-p, 1 KΩ) (using the 1st audio input) |
| Audio output | 1-ch, RCA (Linear, 1 KΩ) |
| Synchronous Playback | 1-ch |
| Frame rate | Main stream: 5 MP@12fps / 4 MP@15fps / 3 MP@18fps 1080p / 720p / WD1/4CIF / VGA / CIF@25fps (P) / 30fps (N), Sub-stream: WD1 / 4CIF / CIF@25fps (P) / 30fps (N) |
| Video bit rate | 32 Kbps to 10 Mbps |
| Audio bit rate | 64 Kbps |
| Alarm in/Alarm out | 1/1 |
| Power supply | 12 VDC |
| Consumption | ≤ 15 W |
| Dimension(W×D×H) | 162.5 × 114 × 47.5 mm |
| Weight | ≤ 1.5 Kg |
| Working temperature | -10°C~+55°C |
| Working humidity | 10% to 90% |

OTHER MODELS

| | |
|------------|---------------------------------------------|
| 2310111139 | DS-6704HWI Four channel Video to IP encoder |
|------------|---------------------------------------------|