

SMT-3233 32 inch Monitor LED Full HD Image

2310120110

SMT-3233 32 inch Monitor LED Full HD

32" Monitor

- ✓ Supports up to 1,920 x 1,080 resolution
- ✓ Contrast ratio 1,200 : 1
- ✓ HDMI, DVI, VGA, BNC

Description

The SMT-3233 32 inch Monitor LED Full HD supports up to 1,920 x 1,080 resolution with a contrast ratio of 1,200 :1. It has a fast response time of 8ms and panel life of 30,000 hours.

Technical Dimensions



Specifications

DISPLAY

Screen Size	31.5"
Max. Resolution	1,920 x 1,080
Brightness	350 cd/m2
Contrast Ratio	1,200 : 1
Aspect Ratio	16:9
Viewing Angle (H/V)	178° / 178°
Display Color	16.7 million
Response Time	8 ms
Video System	NTSC/PAL
Panel Life	30,000 hours
Filter Type	3D combfilter

INTERFACE

Video	Connector: VGA, DVI, HDMI, BNC
	Connector: Analogue D-sub (15 pin), DVI-D
	Input Signal: 0.7Vpp ±5%
RGB/DVI	Available Format: 640 x 480 @ 60Hz / 72Hz / 75Hz (VGA), 800 x 600 @ 56Hz / 60Hz / 72Hz / 75Hz (SVGA), 1,024 x 768 @ 60Hz / 70Hz / 75Hz (XGA), 1,152 x 864 @ 75Hz, 1,280 x 720 @ 60Hz, 1,280 x 800 @ 60Hz, 1,280 x 1,024@60Hz/75Hz (SXGA), 1,360 x 768@60Hz, 1,440 x 900@60Hz, 1,600 x 900@60Hz, 1,680 x 1,050@60Hz, 1,920 x 1,080@60Hz
HDMI	Available Format: 640 x 480p @ 60Hz, 720 x 480p @ 60Hz, 720 x 576p @ 50Hz, 1,280 x 720p @ 50Hz / 60Hz, 1,920 x 1,080 @ 60Hz, 1,920 x 1,080p @ 60Hz
Audio Connector	3.5 mm Mini phone jack
Audio Output Signal	Loop-through line level (PC only), Speakers : 2 x 2W
Application Support	Remote controller

ON SCREEN DISPLAY

Functions	VESA™ DPM compatible
Language	Chinese (Simplified), English, French, German, Spanish, Dutch, Russian, Arabic

GENERAL

Input Voltage	100 ~ 240V AC (50/60Hz)
Power Consumption	< 50W
Operating Temperature	0°C ~ +40°C
Operating Humidity	10% ~ 80% (Non-condensing)
Dimensions without stand (W x H x D)	728.8 x 433.1 x 51.4 mm
Bezel Size	Top 14.5mm (0.57") / Bottom 25mm (0.98")
Cabinet Color	Black
VESA Mounts Interface	100 x 100 mm