



ITCS-C6, Unit For Calling And Call Reset - Layout

4000019391

ITCS-C6

Call and Reset unit

- ✓ Water resistant (IP56)
- Illuminated Call button (green)
- Illuminated Reset button (red)

Description

ITCS-C6 is water-resistant (IP 56) unit for calling and call reset. Call is done with illuminated green "CALL" push button. When call is done, red bulb situated in "RESET" push button is lighted up. Call reset can be done by that push button. After call is reset, red light goes off. Green bulb in "CALL" push button lights all the time (when system is on), to ensure visibility in dark spaces

Technical	Dimensions

page 1/2

certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is

Specifications

TECHNICAL

Dimensions (WxHxD)	80 x 125 x 58 mm (HxWxD)
Weight	0.27 kg
Cable entry	1 pc. Gland - PG13.5
Power consumption	24VDC / 0.026A

Used With









ITCS-1A-24VDC

Single Call Control Unit, 24 VDC

ITCS-1A-230VAC

Single Call Control Unit, 230 VAC

ITCS-2A-24VDC

Double Call Control Unit, 24 VDC

ITCS-2A-230VAC

Double Call Control Unit, 230 VAC