

UHF Radio 4 Channel Combiner, ZEN-COMB-4CH

UHF Radio Combiner

- ✓ Radio UHF Maritime Combiner
- ✓ 4 channels



Description

The UHF Radio 4 Channel Combiner, ZEN-COMB-4CH is a hybrid combiner with single isolators, an active receiver multicoupler and a duplex filter. As default the combiner is tuned for the maritime frequency band: Base station TX range: 457.5250 - 457.5750 MHz, RX range: 467.5250 - 467.5750 MHz. The combiner is supplied by 12Vdc. EU Outlet adapter 230Vac/12Vdc included

Specifications

GENERAL

Dimensions	19" x 3 HU x 500 mm (483 x 133 x 500 mm)
Weight	7.5 Kg
Front plate color	Black
Connectors	N-female
Temperature range	-30° C to +60° C
Maritime approval	EN/IEC 60945

ELECTRICAL

Frequency Range	406 - 470 MHz
Max. Input power per channel	50W
Max. TX-TX Spacing	2.0 MHz
Min. TX-RX Spacing	5.0 MHz
Insertion loss, TX path	< 8.0 dB
TX-TX Isolation	> 70 dB
ANT-TX Isolation	> 40 dB @ 25° C
RX Isolation in TX band:	
- TX-TX spacing < 0.5 MHz	> 85 dB
- TX-TX spacing > 0.5 MHz	> 65 dB
TX Isolation in RX band:	
RX-RX spacing < 0.5 MHz	> 85 dB
RX-RX spacing > 0.5 MHz	> 65 dB
RX-RX Isolation	> 20 dB
Impedance nom.	50 W
SWR	≤ 1.5
LNA Noise Figure	< 3.5 dB
Gain, RX Path	+/-1 dB
Current consumption	500 mA @ 12 Vdc