

loudspeaker

tbd

SPCF-E-06W-50-EN54

ECONOMY FLUSH MOUNT CEILING SPEAKER

- ✓ CERTIFIED TO EN 54-24
- ✓ HIGH QUALITY AUDIO FOR VOICE AND BACKGROUND MUSIC
- ✓ FLUSH MOUNT CEILING SPEAKER
- ✓ 6W / 100V
- ✓ SIZE 5" (130MM) FULL RANGE CHASSIS
- ✓ QUICK AND EASY MOUNTING
- ✓ COST EFFECTIVE
- ✓ LOW PROFILE
- ✓ POWDER COATED METAL CHASSIS
- ✓ PROTECTIVE PLASTIC DOME



Public Address



Voice Alarm

Commercial Audio

EN54

EN 54 Certified

Description

The SPCF-E-06W-50-EN54 is a 6W 100V flush mount ceiling loudspeaker, which has a 5" (130mm) full-range chassis providing excellent sound quality with speech and background music, and which is certified to EN5 4-24. The speaker is fitted with a 100V transformer which has three power adjustment tapings of 6W, 3W, and 1.5W.

The SPCF-E-06W-50-EN54 has a powder coated metal chassis and grille, with the high quality powder coated finish giving good long-term protection and resistance to corrosion. A protective plastic dome covers the rear of the loudspeaker, and prevents dirt, dust and other debris or foreign objects from contacting the cone or any other part of the loudspeaker rear.

The speaker's enclosure is ingress protection rated to IP21C. As standard the speaker is coloured to match RAL9016 'Traffic White', however the speakers can be supplied in any four-digit RAL or NCS colour, as a special order. Quick and easy ceiling mounting is provided through the use of spring clamps, with a possible ceiling thickness of between 3mm and 45mm. The flat construction method allows a low mounting depth of only 70mm.

There is a metal Firedome available for this loudspeaker as an optional accessory, part number SPAC-FD-E-50, which can be used in place of the speaker's rear plastic dome cover to provide additional resilience to fire

Used With



V2000

PAVA 2000W Power Amplifier
Mainframe (0 amps Pre
Installed)

from site

D150

PAVA 150W Power Amplifier
Module for the V2000 /
INTEGRA

from site

D500

PAVA 500W Power Amplifier
Module for the V2000 /
INTEGRA