

loudspeaker

tbd

## SPRF-06W-65-EN54

### FLUSH CABINET SPEAKER

- ✓ EN 54-24 CERTIFIED
- ✓ HIGH QUALITY AUDIO FOR VOICE AND BACKGROUND MUSIC
- ✓ FLUSH CABINET SPEAKER
- ✓ 6W / 100
- ✓ 6.5" (165mm) FULL-RANGE CHASSIS
- ✓ SHOCK-RESISTANT WHITE ABS FRONT PANEL
- ✓ INGRESS PROTECTION RATED TO IP21C



Public Address



Voice Alarm

Commercial Audio



EN 54 Certified

## Description

The SPRF-06W-65-EN54 is a 6W 100V flush mount loudspeaker which has a 6.5" (165mm) full-range chassis providing excellent sound quality with speech and background music, and which is certified to EN 54-24. The speaker is fitted with a 100V transformer which has three power tapings of 6W, 3W and 1.5W.

The SPRF-06W-65-EN54 has a high-density, shock-resistant white ABS front panel which provides a low resonance sound. The speaker has a powder coated metal grille, with the high quality powder coated finish giving good long-term protection and resistance to corrosion. The enclosure is ingress protection rated to IP21C. The speaker is designed to be flush mounted in walls or suitable ceilings. The 100V loudspeaker line cabling is connected by means of a two-pin ceramic block, and for additional reliability a thermal fuse is provided and the speaker chassis is damp-resistant.

The loudspeaker is optionally available with a DC blocking capacitor fitted, in order to provide compatibility with DC loudspeaker line monitoring systems. The part number for this DC monitoring compatible version is SPRF-06W-25-EN54-DC.

## Used With



V2000

PAVA 2000W Power Amplifier  
Mainframe (0 amps Pre  
Installed)

from site

D150

PAVA 150W Power Amplifier  
Module for the V2000 /  
INTEGRA

from site

D500

PAVA 500W Power Amplifier  
Module for the V2000 /  
INTEGRA