

loudspeaker

tbd

SPRS-S-06W-65

SURFACE MOUNT SPEAKER

- ✓ HIGH QUALITY AUDIO FOR VOICE AND BACKGROUND MUSIC
- ✓ SURFACE MOUNT SPEAKER
- ✓ 6W / 100V
- ✓ 6.5" (165mm) FULL RANGE CHASSIS
- ✓ POWDER COATED METAL CHASSIS AND GRILL

 Public Address  Voice Alarm Commercial Audio

Description

The SPRS-S-06W-65 is a 6W 100V surface mount loudspeaker which has a 6.5" (165mm) full-range chassis providing excellent sound quality with speech and background music. The speaker is fitted with a 100V transformer which has three power adjustment tapings of 6W, 3W and 1.5W.

The SPRS-S-06W-65 has a rectangular powder coated metal chassis and grille, with the high quality powder coated finish giving good long-term protection and resistance to corrosion. The enclosure is ingress protection rated to IP21C and is coloured to match RAL9010 'Pure White'. Surface mounting to a wall or ceiling is simply provided through the use of fixing screws, with the enclosure front attaching to the rear mounting panel with three screws. The 100V loudspeaker line cabling is connected by means of a two-pin ceramic block, and for additional reliability a thermal fuse is provided and the speaker chassis is damp-resistant.

This loudspeaker is optionally available with a DC blocking capacitor fitted, in order to provide compatibility with DC loudspeaker line monitoring systems. The part number for this DC monitoring compatible version is SPRS-06W-65-DC.

Used With

from site

from site



D150

PAVA 150W Power Amplifier
Module for the V2000 /
INTEGRA

D500

PAVA 500W Power Amplifier
Module for the V2000 /
INTEGRA

V2000

PAVA 2000W Power Amplifier
Mainframe (0 amps Pre
Installed)