

loudspeaker

tbd

# SPRS-S-06W-65-EN54

## SURFACE MOUNT SPEAKER

- ✓ EN 54-24 CERTIFIED
- ✓ HIGH QUALITY AUDIO FOR VOICE AND BACKGROUND MUSIC
- SURFACE MOUNT SPEAKER
- 6.5" (165mm) FULL RANGE CHASSIS
- POWDER COATED METAL CHASSIS AND GRILL





Public Address Voice Alarm Commercial Audio



EN 54 Certified

# Description

The SPRS-S-06W-65-EN54 is a 6W 100V surface mount loudspeaker which has a 6.5" (165mm) full-range chassis providing excellent sound quality with speech and background music, and which is certified to EN 54-24. The speaker is fitted with a 100V transformer which has three power adjustment tappings of 6W, 3W and 1.5W.

The SPRS-S-06W-65-EN54 has a rectangular powder coated metal chassis and grille, with the high quality powder coated finish giving good long-term protection and resistance to corrosion. The enclosure is ingress protection rated to IP21C and is coloured to match RAL9010 'Pure White'. Surface mounting to a wall or ceiling is simply provided through the use of fixing screws, with the enclosure front attaching to the rear mounting panel with three screws. The 100V loudspeaker line cabling is connected by means of a two-pin ceramic

block, and for additional reliability a thermal fuse is provided and the speaker chassis is damp-resistant.

This loudspeaker is optionally available with a DC blocking capacitor fitted, in order to provide compatibility with DC loudspeaker line monitoring systems. The part number for this DC monitoring compatible version is SPRS-06W-65-EN54-DC.

# **Used With**

page 1/2



•			
tro	m	CI	t 🔿
HU		- OI	ıc

#### D150

PAVA 150W Power Amplifier Module for the V2000 / INTEGRA

#### from site

### D500

PAVA 500W Power Amplifier Module for the V2000 / INTEGRA

### V2000

PAVA 2000W Power Amplifier Mainframe (0 amps Pre Installed)

page 2/2