

loudspeaker

tbd

## SPCR-06W-50-EN54

### FLUSH MOUNT CEILING SPEAKER

- ✓ EN 54-24 CERTIFIED
- ✓ SIZE 5" (130 MM) CHASSIS
- ✓ HIGH QUALITY AUDIO FOR VOICE AND BACKGROUND MUSIC
- ✓ 6W / 100V
- ✓ FLUSH MOUNT CEILING SPEAKER
- ✓ MAGNETIC FASTENING GRILLE
- ✓ EASY MOUNT CLAMPS
- ✓ PROTECTION IP21C
- ✓ IMPACT RESISTANT ABS
- ✓ WAGO CONNECTORS



Public Address



Voice Alarm

Commercial Audio

**EN54**

EN 54 Certified

## Description

The SPCR-C-06W-50-EN54 is a 6W 100V round frameless ceiling mount loudspeaker, which has a 5" (130mm) full-range chassis providing excellent sound quality with speech and background music, and which is certified to EN54-24. The speaker is fitted with a 100V transformer which has three power adjustment tapings of 6W, 3W, and 1.5W.

The SPCR-C-06W-50-EN54 has a powder coated metal chassis and grille, with the high quality finish giving good long-term protection and resistance to corrosion. The speaker is supplied with a rear fire dome, and its enclosure is ingress protection rated to IP21C. As standard the speaker is coloured to match RAL9016 'Traffic White', however the speakers can be supplied in any four-digit RAL or NCS colour, as a special order.

A screw mounting system is provided for ceiling mounting, with a possible ceiling thickness of between 1mm to 45mm. The 100V loudspeaker line cabling is connected by a WAGO terminal clamp (maximum cable cross section is 4mm<sup>2</sup>), with rubber grommets fitted for cable support. For additional reliability the loudspeaker chassis is damp-resistant.

The loudspeaker is optionally available with a DC blocking capacitor fitted, providing compatibility with DC loudspeaker line monitoring systems. The part number for this DC monitoring compatible version is SPCR-06W-50-EN54-DC.

## Used With



V2000

PAVA 2000W Power Amplifier  
Mainframe (0 amps Pre  
Installed)

from site

D150

PAVA 150W Power Amplifier  
Module for the V2000 /  
INTEGRA

from site

D500

PAVA 500W Power Amplifier  
Module for the V2000 /  
INTEGRA