

T91-2000\_UPS\_FRONT

1000291

## UPS-XPC-1900-120T

Tower Online UPS 1900W/30 min, 120V

- ✓ Tower Online UPS
- ✓ 120VAC
- ✓ 1900W / 30 min
- ✓ Double-conversion online design

### Description

T91 UPS provides double conversion online power for light industrial applications, point of sale, servers and voice & data networks. T91 features unity output power factor to support up to 43% more critical loads than typical UPSs.

- ✓ UL, cUL, CE, RoHS, FCC B, FCC A
- ✓ T91 provides industry highest real power rating
- ✓ Extended battery packs for runtimes up to 4 hours
- ✓ Fast Recharge: up to 95% in just 3 hours
- ✓ Multiple communications capability
- ✓ Load shedding capabilities
- ✓ Emergency power off

Item UPS-XPC-1900-120T consists of:

- ✓ 1x T91-3000 (the UPS)
- ✓ 1x T91-BP72A (Battery pack)

### Technical Dimensions




# Specifications

## GENERAL

Input Power rating	3000VA (2880W)
Input Voltage	55-150VAC
Input Frequency	50/60Hz auto-sensing
Output Voltage	120VAC nominal (100/110/115/127 selectable)
Frequency	50/60Hz auto-sensing $\leq$ 1%
Efficiency	Up to 98% ECO Mode and 92% online mode
UPS, Dimensions	7.4" x 16.5" x 12.5" (18.8 x 41.9 x 31.8 cm) (W x D x H)
UPS, Weight	66 lbs (29.94 kg)
Battery type (included)	Up to 30 minutes
Battery Dimensions	7.4" x 16.5" x 12.5" (18.8 x 41.9 x 31.8 cm) (W x D x H)
Battery, Weight	82 lbs (37.19 kg)

## Accessories



### UPS-XPC-CARD

Dry Contact Interface Card