VINGTOR STENTOFON


Replacing Amplifier Module on ENA2200

Item Number	Item Name	Description
102 3922 200	EAM-200	Exigo 2x200 Watt Amplifier Module for ENA2200

1 Accessing the Old Amplifier Module

Before you start the procedure:

- 1. Switch off and disconnect the amplifier from the power mains
- 2. Remove the top cover by unscrewing the 8 Torx screws using a T10 bit





When the top cover is removed, you will see the Amplifier Module located at the side of the amplifier cabinet.

2 Demounting the Old Amplifier Module

The Amplifier Module is plugged into the Euroconnector at the bottom of the cabinet and secured with four M4 screws as shown:



To demount the Amplifier Module:

- 1. Use a PZ2 bit to unfasten and remove the four M4 screws
- 2. Pull the Amplifier Module up to unplug it from the Euroconnector at the bottom of the cabinet
- 3. Lift the Amplifier Module out of the cabinet

3 Installing the New Amplifier Module

- 1. Align the Amplifier Module with the four screw holes
- 2. Press the Amplifier Module down to plug it into the Euroconnector at the bottom of the cabinet



- 3. Use a PZ2 bit to fasten the four M4 screws and secure the Amplifier Module to the cabinet
- 4. Put the top cover back in place and fasten with the 8 Torx screws



After the new Amplifier Module has been powered up and you happen to remove it, DISCHARGE the large capacitors BEFORE inserting it back in.

DOC NO.



22.12.201

customer.service@zenitel.com

