

**Braunschweig und Berlin** 

(1)

(5)



## **EC-TYPE-EXAMINATION CERTIFICATE**

(Translation)

- (2)Equipment and Protective Systems Intended for Use in Potentially Explosive Atmospheres - Directive 94/9/EC
- (3)EC-type-examination Certificate Number:



#### PTB 99 ATEX 2115

Second telephone alarm and signal unit TWIN-EEXII type 5842/1 (4)Equipment:

Funke+Huster Fernsig Fernsprech-und Signalbau GmbH & Co.KG Manufacturer:

D-42551 Velbert (6)Address:

- This equipment and any acceptable variation thereto are specified in the schedule to this certificate and (7) the documents therein referred to.
- The Physikalisch-Technische Bundesanstalt, notified body No. 0102 in accordance with Article 9 of the (8)Council Directive 94/9/EC of 23 March 1994, certifies that this equipment has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of equipment and protective systems intended for use in potentially explosive atmospheres, given in Annex II to the Directive.

The examination and test results are recorded in the confidential report PTB Ex 99-29119.

Compliance with the Essential Health and Safety Requirements has been assured by compliance with: (9)

EN 50014:1997

EN 50019:1994

EN 50020:1994

EN 50028:1987

- (10) If the sign "X" is placed after the certificate number, it indicates that the equipment is subject to special conditions for safe use specified in the schedule to this certificate.
- (11) This EC-type-examination Certificate relates only to the design and construction of the specified equipment in accordance with Directive 94/9/EC. Further requirements of this Directive apply to the manufacture and supply of this equipment.
- (12) The marking of the equipment shall include the following:

II 2 G EEx [ib] em IIC T6

Zertifizierungsstelle Explosionsschutz

By order:

Braunschweig, July 16, 1999

Dr.-Ing. U. Johannsn

Regierungsdirektor

sheet 1/2



### **Braunschweig und Berlin**

(13)

## SCHEDULE

## (14) EC-TYPE-EXAMINATION CERTIFICATE PTB 99 ATEX 2115

### (15) Description of equipment

The second telephone alarm and signal unit TWIN-EExII type 5842/1 is particularly constructed for the application in explosion hazardous industrial areas and permits the operation inside of buildings or in open air environments. The TWIN-EExII can be switched to the operating modes telephone alarm and optical alarm signal by a slide switch inside the apparatus.

#### Electrical data

Terminals mains supply 230 V/50 Hz (N-mains and L1-mains) +10%/-15%

fuse to be connected in series 500 mA

resp.

mains supply 120 V/50 Hz +10%/-10%

fuse to be connected in series 8

800 mA

Telephone terminal connection calling alternating voltage  $U \le 165 \text{ V}$  (terminals W and Lb) supplying direct voltage  $U \le 60 \text{ V}$ 

The terminals W and Lb may only be connected to a telephone for operation with master and slave stations or directly to the telephone network. The short-circuit protection is carried out in the mentioned stations. The limitation must correspond to the max. rated current (permissible  $3 \times I_N$ ).

Internal intrinsically safe circuits of category "ib" on the master board

speaker terminal signal terminal slide switch S1

Internal non-intrinsically safe circuit

flash board

- (16) Test report PTB Ex 99-29119
- (17) <u>Special conditions for safe use</u> not applicable
- (18) Essential health and safety requirements

met by the standards mentioned above

Zertifizierungsstelle Explosie By order:

Braunschweig, July 16, 1999

Dr.-Ing. U. Johannsmey

Regierungsdirektor

sheet 2/2



Braunschweig und Berlin

#### 1. SUPPLEMENT

according to Directive 94/9/EC Annex III.6

#### to EC-TYPE-EXAMINATION CERTIFICATE PTB 99 ATEX 2115

(Translation)

Equipment:

Second telephone alarm and signal unit TWIN-EEXII, type 5842/1

Marking:

EEx [ib] em IIC T6

Manufacturer: Funke + Huster Fernsig GmbH

Address:

Gewerbeallee 15-19, 45478 Mülheim an der Ruhr, Germany

#### Description of supplements and modifications

The mother board of the second telephone alarm and signal unit TWIN-EEXII, type 5842/1 may be potted with another type of casting compound to form an encapsulated module. In this case the 2-component epoxy casting compound, type Rhenatech EP 5470 FR with the appropriate hardener, type EP 5710 is used.

All further specifications of the EC-type examination certificate apply without changes.

Applied standards

EN 50014:1997 + A1 + A2

EN 50019:2000

EN 50020:1994

EN 50028:1987

Test report:

PTB Ex 05-25320

Zertifizierungsstelle Explosio

By order;

Dr.-Ing. U. Johannsmey

Direktor und Professor

Braunschweig, December 8, 2005

Sheet 1/1



Braunschweig und Berlin

### 2. SUPPLEMENT

according to Directive 94/9/EC Annex III.6

#### to EC-TYPE-EXAMINATION CERTIFICATE PTB 99 ATEX 2115

(Translation)

Equipment:

Second telephone alarm and signal unit TWIN-EEXII, type 5842/1

Marking:

EEx [ib] em IIC T6

Manufacturer: FHF Funke + Huster Fernsig GmbH

Address:

Gewerbeallee 15-19, 45478 Mülheim an der Ruhr, Germany

#### Description of supplements and modifications

The type labels may alternatively be made of the materials Polymatic 25 and Polymatic 50 manufactured by the company Wölco AG.

In the future the equipment shall be marked as follows:

II 2 G Ex mb e [ib] IIC T6

The requirements of the standards listed below are complied with by this supplement.

The "Special Conditions" of the EC-type examination certificate apply also to this supplement.

Applied standards

EN 60079-0:2006

EN 60079-7:2007

EN 60079-11:2007

EN 60079-18:2004

Test report: PTB Ex 08-27171

Zertifizierungsstelle

By order:

Braunschweig, March 11, 2008

Dr.-Ing./U. Gerlach Oberregierungsrat

Sheet 1/1



Braunschweig und Berlin

#### 3. SUPPLEMENT

according to Directive 94/9/EC Annex III.6

### to EC-TYPE-EXAMINATION CERTIFICATE PTB 99 ATEX 2115

(Translation)

Equipment:

Secondary telephone alarm and signal unit TWIN-EEXII, type 5842/1

Marking:

II 2 G Ex mb e [ib] IIC T6

Manufacturer: FHF Funke + Huster Fernsig GmbH

Address:

Gewerbeallee 15-19, 45478 Mülheim a.d. Ruhr, Germany

### Description of supplements and modifications

A new casting compound is applied to the potting form containing the p.c.b. with the electronicflash lamps. The ambient temperature range is extended to + 60 °C.

In the future the equipment shall be marked corresponding to the ambient temperature range as follows.

for  $-20^{\circ}$ C  $\leq T_a \leq +40^{\circ}$ C

(£x) II 2 G Ex e mb [ib] IIC T6 Gb

for  $-20^{\circ}$ C  $\leq T_a \leq +50^{\circ}$ C

⟨Ex⟩ II 2 G Ex e mb [ib] IIC T5 Gb

for  $-20^{\circ}$ C  $\leq T_a \leq +60^{\circ}$ C

⟨Ex⟩ II 2 G Ex e mb [ib] IIC T4 Gb

When the equipment is used at ambient temperatures > 40°C it is only suitable for a lower grade of mechanical stress.

#### Applied standards

EN 60079-0:2009, EN 60079-7:2007, EN 60079-11:2007, EN 60079-18:2009

Test report:

PTB Ex 12-21102

Zertifizierungszektor Explosionsschutz

On behalf of #

Direktor und Profes

Braunschweig, March 29, 2012

Sheet 1/1